TC193

Reclining Type Deluxe Right Auxiliary Arm Tire Changer

Scan for more information

TC193 Reclining Type Deluxe Right Auxiliary Arm Tire Changer significantly enhances efficiency, safety, and adaptability in tire servicing, particularly excelling in handling specialized tires such as run-flat and wide-base tires.



Metal six-bar gland

Pneumatic locking button

Tilt-back design

Air inflation+toolbox

Deluxe three points pressing mechanical arm

Enhanced base

Huge turntable suits to mount tires up to 24”

Oil-water seperator for exporting

Large and durable tire bead break pad

Post Tilt Pedal, Mounting Head Pedal, Demount Arm Pedal, Turntable Pedal

Features

1. Advanced mechanical arm , the pulley part of the form of a set, embedded wear-resistant sliding block, with fine grinding square tube, so that the mechanical arm can run smoothly and freely;
2. All joints of the auxiliary arm are mounted with vertebral bearings, smooth and smooth without lag;
3. Thicker working palte, precision cast steel material claw, non-skid durable claw claw protection cover, high quality all-aluminum small cylinder;
4. Tire removal structure, thickened shovel arm body, universal large shovel, high-quality large shovel protective cover, anti-slip rubber plate;
5. The all-aluminum air cylinder can reduce machine vibration and minimize friction, thereby extending the service life of the cylinder;
6. Special explosion-proof grade oil mist device,good pressure resistance effect and high safety factor;
7. Optional automatic flip of the bird head.

Parameters

Rim Diameter Range	10-22" (Outer clamping size) 12-24" (Inner clamping size)
Max Tire width	13" (330mm)
Max tire diameter	39" (1000mm)
Working air pressure	8-10bar
Operating panel speed	7rpm
Bead Breaker Pressure	2500kgf

voltage	110V/220V/380V
Power	0.75/1.1Kw
Net weight / Gross weight	300/346kg
package size	1070×980×1200mm
container loading quantity	20GP-15pcs 40HQ-48pcs







Standard Configuration

- 24" working plate
- Stainless steel working head
- Push down assistant arm
- Enhanced bead breaker arm
- Oil-water seperator for exporting
- Air inflation indicator +toolbox
- Enhanced base
- Metal hexagonal compression cap

Optional Accessory

- Automatic working head
- Power assisted handle
- Motorcycle-specific fixture
- Variable-speed motor 220V
- Two-speed motor 380V / Speed 6.5/13 rpm
- Cylinder-type jaw breakage
- Hand held explosive tank
- Automatic inflation gauge
- Power assisted handle
- Single exhaust all-aluminum cylinder
- Aluminum injection-molded footrest
- Stock market protection cover